
SPECTRATILE® CEILING TILE





Finalé

100% WATERPROOF CEILING TILE

It's a truly spectacular lay-in ceiling that stays that way, day after day... year after year. With an extended product life and one year warranty, it's a permanent, low maintenance solution to common lay-in ceiling problems. It's non-absorbent and will not swell, bow or rot. It won't harbor bacteria and it's mold and mildew resistant. It can be scrubbed and even pressure washed. SPECTRATILE Tiles Can Save Money on Lighting, With Their Excellent Light Reflectance Values. There are no special coatings or surface sealants needed to resist stains or withstand harsh conditions. SPECTRATILE. It's every bit as spectacular as it sounds. See for yourself at www.parklandplastics.com.

100% WATERPROOF

Acoustic

- · No water damage or staining
- Non-absorbent, no swelling, bowing or rotting
- · Will not harbor bacteria
- · Mold and mildew resistant

FUNCTIONAL

- Class A, per ASTM E-84
- Passes UL1715 room corner burn test

Millennium

NRC for the acoustic tile is .52

Fissured

GREENGUARD Certified

COST EFFECTIVE

Repertoire

- Extended product life
- Permanent replacement solution
- · Improve and reduce your overhead

Stucco

Low maintenance

LIGHT REFLECTANCE

Wave

• Finalé 85%

Tegular

• Millennium 81%

Repertoire 82%

PRODUCT COMPARISON CHART

FEATURES	SPECTRATILE	VINYL-CLAD GYPSUM-CORE	FIBER-BASED TILE
Zero Water Absorbance	х		
Guaranteed Against Water Stains	х		
Resists Mold, Mildew, Bacteria Growth	х	х	
Perfect Score for ASTM Mold Resistance Test	х		
Will Not Flake, Break or Create Dust	х		
Impact Damage Resistant	х		
May be Pressure Washed or Scrubbed	х	х	
Sound Absorbent	X*		х
Decorative Patterns	х		х
Passes IBC 2603.9	х		

In the chart to the left, SPECTRATILE is compared to data obtained for traditional ceiling tiles that are commonly available at retail outlets. The comparisons are general in nature and do not refer to any specific manufacturer's products. The comparisons are based upon independent tests and various manufacturers' published product specifications.



SPECTRATILE USE AND CARE

SPECTRATILE can be installed in a standard grid. It can be cut with a circular saw and in some cases with a utility knife. For tight cuts use a jig saw or a Rotozip.

It can be taken down and washed without damage, and since SPECTRATILE is non-absorbent it can be power washed. Most strong cleaners like Simple Green® will not damage the surface, but it is always best to try an inconspicuous corner first.

Complete care and maintenance instructions are available on www.parklandplastics.com.

SPECTRATILE PROPERTIES

ASTM E-84	Flame Spread	25 or Less	
ASTM E-84	Smoke Development	Less than 450	
Weight	Pounds/SF	.6	
ASTM D 3273	Mold/Mildew Resistance	1-10 / 10 Best	
Ion Chromatography	VOC Content	0	
Ion Chromatography	Corrosive Content	0	



^{*}SPECTRATILE Acoustic is sound absorbent. Fissured pattern is printed on the tile.